





## Technical Specifications...

	WM-Nano 'M' Type	WM-Nano 'L' Type
Packs Per Minute:	15ppm	
Wrapping Capacity:	20g-1500g	20g-3500g
Weighing Capacity:	20g-6000g	40g-15000g
Wrapping Size:	Depth: 90~210mm (3.5"~8.3"); FP: 80mm (3.15") Width: 150~330mm (5.9"~13"); FP: 120mm (4.72") Height: 10~130mm (0.4"~5.1") Tray height: ≤45mm (1.8") Note: It is not possible to achieve all three maximum dimensions contemporary on the machine. FP means Foot Print size of the tray (bottom size).	Depth: 127~254mm (5"~10"); FP: 80mm (3.15") Width: 150~350mm (5.9"~13.8"); FP: 120mm (4.72") Height: 10~130mm (0.4"~5.1") Tray height: ≤45mm (1.8") Note: It is not possible to achieve all three maximum dimensions contemporary on the machine. FP means Foot Print size of the tray (bottom size).
Tray:	PSP, PP	
Film Type:	Poly or PVC	
Film Size:	350 · 400 · 450mm (13.78" · 15.75" · 17.72") Max. φ: 165mm (6.5")	400 · 450 · 500 · 550 · 560mm (15.75" · 17.72" · 19.69" · 21.65" · 22.05") Max. φ: 200mm (7.9")
Power:	Voltage: 220~240V Frequency: 50/60Hz	
Operating Temperature:	5°C~35°C (41°F~95°F)	
Humidity:	20%~85% R.H.	
Weight:	Wrapper: 90kg; Wrapper & scale: 100kg	
Noise:	73db	

 **ISHIDA**

Specifications and design are subject to change without notice.

 **ISHIDA CO., LTD.**

44 SANNO-CHO, SHOGOIN, SAKYO-KU  
 KYOTO, 606-8392 JAPAN  
 PHONE: 81-75-771-4141  
 FACSIMILE: 81-75-751-1634  
 URL: <http://www.ishida.com>

