

Magellan® 8400

Performance, Quality and Value



Features:

- Enhanced All-Weights® Platter
- Aggressive and ergonomic 360° 5-sided scanning
- Multiple interface solution supports all popular host interfaces
- FirstStrike® advanced decoding software
- Flash memory for easy, low cost upgrades
- Powered auxiliary RS-232 port for easy integration of a handheld scanner
- GSI DataBar™ (RSS) decoding
- Optional EAS functionality
- Integrated Produce Lift Bar or Produce Rail™
- Value Added Features:
 - Host Download
 - Diagnostic Reporting
 - Productivity Index Reporting™ (PIR)
 - Cashier Training™



Mechanical

Length

Model	Scanner/Scale	Length
8401	Short scanner	35.3 cm / 14.0 in
8402	Medium scanner	39.9 cm / 15.8 in
8403	Long scanner	50.8 cm / 20.0 in
8404	Med. scanner/scale	39.9 cm / 15.8 in
8405	Long scanner/scale	50.8 cm / 20.0 in

Width: 29.2 cm / 11.5 in

Depth (below counter): 10.0 cm / 4.0 in

Height (above counter): 131 cm / 51 in

Scale Capacities

Capacity: 15 kg / 30.0 lb

Minimum Increment: 0.005 kg / 0.01 lb

Vibration Immunity: 4 programmable filter settings

Maximum Static Weight: 68 kg / 150 lb

Adjustments Required: Calibration only

Optical

Scan Lines: 52

Motor Speed: 6,000 rpm

Scan Rate: 5,200 lines/sec.

Scan Zone: 360°

Sides Read: 5

Read Height: 15.2 cm / 6.0 in

Environmental

Temperature Rating:

Operating: 10 to 40 °C / 50 to 104 °F

Storage: -40 to 70 ° / -40 to 158 °F

Humidity: 5 to 95% NC

Decoding Capability

The Magellan® 8400 autodiscriminates between the following supported symbologies:

- UPC Versions A & E
- UPC Supplementals (Bookland & Coupon Code)
- UPC Add-ons (sub 2, sub 5 & C128)
- EAN 8, 13
- JAN 8, 13
- EAN/JAN two label
- UCC/EAN 128
- Code 39 (with full ASCII)
- Code 128
- Code 93
- Interleaved 2 of 5
- Italian Pharmacode
- Codabar/NW7
- MSI/Plessey
- GSI DataBar™ (RSS)

Data Sheet

Electrical

AC Power requirements:

100-250 VAC, 50-60 Hz

7 Watts (nominal)

8 Watts (maximum)

4 Watts (sleep mode)

Communications

Host: All Magellan® 8400 models support IBM 46XX, RS-232, OEM USB, Dual RS-232 scanner-scale, and Keyboard Wedge and USB for scanner only models.

Other:

Powered RS-232 auxiliary port

Scale host port

Remote scale display port


EAS port

Safety & Regulatory

Electrical: IRAM (Argentina), AS/NZS 60950 (Australia); CSA-C22.2 No. 60950 (Canada); EN60 950 (TÜV Europe); PSE Mark (Japan); UL 60950 (USA); BSMI Taiwan

Emissions: FCC part 15, Class A (USA); AS/NZS 3548 (Australia/New Zealand); EN 55022-B (Europe); CISPR 22-B, VCCI-B (Japan)

Laser Safety: Class IIa Laser Product

 (CAUTION: Laser Light – do not stare into beam); IEC 825 Class 1, EN60 825 Class (Europe)

Restriction of Hazardous Substances: Complies to EU RoHS



Weights and Measures: Argentina; Australia; Brazil; Canada; 90/384/EEC (Europe); Mexico; New Zealand; USA (NIST Handbook 44)

Contact your Datalogic Scanning representative for certification schedule and additional listings.

Other

EAS Compatibility: Integrated EAS hardware will work with Counterpoint IV, V, VI, and VII models available from Checkpoint® Systems. Sensormatic® compatible.

Good Read acknowledgement with Sensormatic® and Checkpoint® Systems.



DATALOGIC™



Proudly Sold & Serviced By:

Able Scale Co Pty Ltd

Ph: 1300 731 360

21 Green St Thomastown VIC. 3074

find us on the web: www.ablescale.com.au



Copyright © Datalogic Scanning, Inc. 2007/2008. All rights reserved. Protected to the fullest extent under U.S. and international laws. Copying, or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc. • Datalogic Scanning, Inc. of Eugene, Oregon, USA is ISO registered by NQA. • Datalogic is a registered trademark of Datalogic S.p.A. in many countries and the Datalogic logo is a trademark of Datalogic S.p.A. • Magellan, All Weighs and FirstStrike are registered trademarks of Datalogic Scanning Inc. • OmegaTek, Productivity Index Reporting (PIR), Produce Rail and Cashier Training are trademarks of Datalogic Scanning Inc. • All other brand and product names are trademarks of their respective owners. • Additional information concerning this product or other Datalogic products and services can be found at the Datalogic web site: www.scanning.datalogic.com. • Product specifications are subject to change without notice.

R40-Q293-UK US-C 0508